

BLANK PAGE



IS: 11510 - 1985

Indian Standard

SPECIFICATION FOR SPINDLE FOR JUTE COP WINDING MACHINE

UDC 677.053.237 : 677.053.292 - 229.3



@ Copyright 1986

INDIAN STANDARDS INSTITUTION
MANAK BHAVAN, 9 BAHADUR SHAH ZAFAR MARG
NEW DELHI 110002

Indian Standard

SPECIFICATION FOR SPINDLE FOR JUTE COP WINDING MACHINE

Jute Mill Accessories and Jute Machinery Spare Parts Sectional Committee, TDC 17

Chairman

SHRT R. C. PANI

Representing

Lagan Jute Machinery Co Ltd, Calcutta

Members

SHRI P. K. BOSE (Alternate to

Shri R. C. Pani)

DR AKASH CHANDRA

SHRI P. G. GUPTA (Alternate)

SHRI A. K. BANERJEE SHRI R. P. CHATTERJEE (Alternate)

SHRI B. R. BASU

SHRI G. C. CHATTERJEE SHRI H. N. GHOSH

SHRI R. N. THAKAR (Alternate)

SHRIS, P. GOVAL

SHRID. GUPTA

SHRI T. K. ROYCHOWDHURY (Alternate)

SHRI D. S. JAIN SHRI S. K. GHOSH (Alternate)

SHRI K. M. MODI

SHRI G. D. JOSHI (Alternate) SHRIP. C. MOHUNTA

SHRI SITA RAM PODDAR Dr S. R. RANGANATHAN

SHRI D. P. KHATUA (Alternate) REPRESENTATIVE

REPRESENTATIVE

REPRESENTATIVE

Forest Research Institute & Colleges, Dehra Dun

Britannia Engineering Co Ltd, Titagarh

Office of the Jute Commissioner, Calcutta Braithwaite & Co Limited, Calcutta

Indian Jute Mills Association, Calcutta

Association of Merchants & Manufacturers of Textile Stores & Machinery (India), Bombay Jute Manufacturers Development Council,

Calcutta; and New Central Jute Mills Co Ltd, Calcutta

Shalimar Group Private Ltd, Howrah

Indian Pin Manufacturing Co. Calcutta

Birla Jute & Industries Ltd, Birlapur

Hindustan Bobbin Industries, Calcutta Indian Jute Industries' Research Association,

Calcutta

Textile Machinery Manufacturers Association (India), Bombay

Swadeshi Jute Machinery Corporation Ltd, Calcutta

Export Inspection Council of India, Calcutta

(Continued on page 2)

Copyright 1986

INDIAN STANDARDS INSTITUTION

This publication is protected under the Indian Copyright Act (XIV of 1957) and reproduction in whole or in part by any means except with written permission of the publisher shall be deemed to be an infringement of copyright under the said Act.

IS: 11510 - 1985

(Continued from page 1)

Members

SHRI S. M. TIWARI SHRI R. I. MIDHA. Director (Tex)

Representing

Thomas Duff & Co (India) Ltd, Calcutta Directorate General, ISI (Ex-officio Member)

Secretary SHRI P. BHATNAGAR Assistant Director (Tex), ISI

Jute Mill Accessories and Jute Machinery Spare Parts Subcommittee, TDC 17:2

Convener

SHRI D. P. KHATUA

Indian Jute Industries Research Association. Calcutta

Members

SHRI S. K. NEOGI (Alternate to Shri D. P. Khatua) DR AKASH CHANDRA

SHRI P. G. GUPTA (Alternate)

SHRI A. K. BANERJEE

SHRI R. P. CHATTERJEE (Alternate)

SHRI A. N. BISWAS

SHRI I. CHARRABARTI (Alternate)

SHRI P. K. CHAUDHURI SHRI P. L. DAS GUPTA (Alternate)

SHRI ASIT CHATTERJEE

SHRI ALOKE ROY (Alternate) SHRI D. K. DUTTA SHRI K. K. DAS (Alternate)

SHRI S. K. DUTTA

SHRI G. MITRA (Alternate)

SHRI A. K. GUPTA SHRI D. GUPTA

SHRI D. S. JAIN

SHRI S. K. GHOSH (Alternate) SHRI R. C. PANI

SHRI P. K. BOSE (Alternate) REPRESENTATIVE

REPRESENTATIVE

Shri R. K. Sanganaria

SHRI P. K. CHATTERJEE (Alternate)

SHRI R. N. THAKAR

Forest Research Institute & Colleges, Dehra Dun

Britannia Engineering Co Ltd, Titagarh

Guest, Keen, Williams Ltd, Howrah

India Machinery Co Ltd, Howrah

Industrial Engineers India, Panihati, Dist 24 Parganas

Office of The Jute Commissioner, Calcutta

Export Inspection Council of India, Calcutta

New Central Jute Mills Co Ltd. Calcutta Iute Manufacturers Development Council. Calcutta

Shalimar Group Private Ltd, Howrah

Lagan Jute Machinery Co Ltd, Calcutta

Swadeshi Jute Machinery Corporation Ltd. Calcutta

Machinecare & Consultants, Calcutta

Utex Industries, Calcutta

Indian Jute Mills Association, Calcutta

Indian Standard

SPECIFICATION FOR SPINDLE FOR JUTE COP WINDING MACHINE

0. FOREWORD

- 0.1 This Indian Standard was adopted by the Indian Standards Institution on 10 December 1985, after the draft finalized by the Jute Mill Accessories and Jute Machinery Spare Parts Sectional Committee had been approved by the Textile Division Council.
- 0.2 This standard has been published in order to provide the guidance to the manufacturers of spindles for jute cop winding machines so that spindles of acceptable quality are available to the jute industry. This would ensure higher productivity due to better interchangeability of spindles in the winding machine and its smooth functioning.
- 0.3 For the purpose of deciding whether a particular requirement of this standard is complied with, the final value, observed or calculated, expressing the result of a test or analysis, shall be rounded off in accordance with IS: 2-1960*. The number of significant places retained in the rounded off value should be the same as that of the specified value in this standard.

1. SCOPE

1.1 This standard prescribes the requirements of spindle for cop winding machine in a jute mill.

2. MANUFACTURE

- 2.1 Material The spindle shall be manufactured from carbon steel designation 55C8 as per IS: 1570 (Part II)-1979†.
- 2.2 Finish The spindle shall be ground finish. The tappering shall not exceed 1 in 100.


^{*}Rules for rounding off numerical values (revised).

[†]Schedules for wrought steels: Part II Carbon steel (unalloyed steel) (first revision).

3. REQUIREMENTS

3.1 Dimensions

- 3.1.1 The nominal dimensions of the spindle shall be as agreed to between the manufacturer and purchaser or in the absence of any agreement, the nominal dimensions would be as declared by the manufacturer.
- 3.1.2 Tolerances The dimensional requirements of the spindle shall be subject to the following tolerences (see Fig. 1).



Spindle Dimension	Tolerance in (mm)
\mathbf{A}	± 0·75
В	± 0·05
C	± 0·05
φ D ₁	— 0.02 5
Ψ 1.1	— 0.07 5
$\phi \mathbf{D}_2$	+ 0.00
φD_2	- 0.01
E	± 0·05
${f F}$	± 0·05
G	— 0 ·05
G	— 0 10
H	+ 0.10
11	- 0.00
T	+ 0.05
J	- 0.0 0

Fig. 1 Spindle for Jute Cop Winding Machine

- 3.2 Hardness Spindle shall have hardness of 25 to 32 HRC.
- **3.2.1** Hardness shall be determined by method prescribed in IS: 1586-1968*.
- 3.3 Run-Out The run-out of spindle shall not exceed 0.05 mm.
- 3.4 Eccentricity The eccentricity of spindle shall not exceed '05 mm.

4. MARKING

- **4.1** Unless otherwise agreed between the buyer and manufacturer, each spindle shall be legibly marked with the manufacturer's name or trade-mark.
- **4.1.1** ISI Certification Marking Spindles may also be marked with the ISI Certification Mark.

Note—The use of the ISI Certification Mark is governed by the provisions of the Indian Standards Institution (Certification Marks) Act and the Rules and Regulations made thereunder. The ISI Mark on products covered by an Indian Standard conveys the assurance that they have been produced to comply with the requirements of that standard under a well-defined system of inspection, testing and quality control which is devised and supervised by ISI and operated by the producer. ISI marked products are also continuously checked by ISI for conformity to that standard as a further safeguard. Details of conditions under which a licence for the use of the ISI Certification Mark may be granted to manufacturers or processors, may be obtained from the Indian Standards Institution.

5. SAMPLING AND CRITERIA FOR CONFORMITY

- 5.1 Lot In a consignment, all the spindles of the same type and manufactured under the same conditions shall constitute a lot.
- 5.1.1 For conformance of this specification, samples shall be drawn from the lot in accordance with Table 1.

TABLE 1 NUMBER OF SPINDLES TO BE SELECTED FOR SAMPLING

LOT SIZE	SAMPLE SIZE	Acceptance Number	Sub-Sample Size
(1)	(2)	(3)	(4)
Up to 150	8	1	2
151,, 300	13	2	2
301,, 500	20	3	2
501,,1000	32	5	3
1001 and above	50	7	3

^{*}Method of Rockwell hardness test (B & C scales) for steel (first revision)

IS: 11510 - 1985

5.2 Number of Test

- 5.2.1 All the spindles in the sample shall be visually examined for material and finish.
- 5.2.2 For requirements given in 3.1, 3.3 and 3.4 the spindles selected in the sample shall be tested. Hardness (3.2), shall be tested on the sub-sample given in col 4 of Table 1.

5.3 Criteria for Conformity

5.3.1 Whenever a spindle fails to meet any of the requirements given in 3.1, 3.3 and 3.4 it shall be declared as defective. The lot shall be declared as conforming to the requirements of 3.1, 3.3 and 3.4 if the number of defective spindles does not exceed the corresponding acceptance number; and for requirements of 3.2 none of the spindles tested on the sub-sample shall fail.

6. PACKING

6.1 Spindles shall be packed in such a way so as to ensure complete protection from rust and bending.